The Model 9112i is a value priced, basic single line IP Telephone with speakerphone offering a flexible, interoperable IP solution that meets VoIP budgets for most applications.



# Model 9112i IP Telephone

#### **Key Features:**

- Enhanced Call Management Large storage for personal directory, callers log, and redial list
- Tight Integration Support for multiple IP telephony systems including BroadWorks<sup>®</sup>, Nortel, Sylantro, and Asterisk SIP
- Remarkable Audio Quality speakerphone with excellent voice delivery
- **Protect Your Investments** Firmware upgrades can be downloaded and installed in the field as standards develop and protocols evolve

flexible integrated upgradeable





## Building success with the business telephone leader

VIEW A

TELECOM

THE INT

T WWW.AASTRA.CO

#### **Technical specifications**

#### Physical

- » 20.2 cm W x 19.2 cm D x 8.9 cm H (8.0"W x 7.6"D x 3.5"H)
- » 812 g (28.6 oz)

#### Power

» AC wall adapter included

#### Handset / Headset

- » Modular RJ9 headset connector, compatible with amplified business headsets
- » Hearing aid compatible handset
- » Quality speakerphone

#### Display

» 3 line backlit display

#### Feature Keys

- » 4 navigational keys
- » 2 programmable keys
- » 11 predefined hard keys including Callers log, Conference, Call Transfer, Redial, Options, Directory, Save, Delete, Speaker/Headset, Mute

#### Networking

- » 10/100 Mbps Ethernet port
- » Manual or Dynamic Host Configuration Protocol (DHCP) IP address setup
- » Time and date synchronization using SNTP
- » Built-in HTTP server for web administration and maintenance
- » Server provisioned user configuration files

THIRD-PARTY INTEROPERABILITY	480i CT	480i	9133i	9112i
SPHERE COMMUNICATIONS - SPHERICALL MGCP		*		
BROADSOFT <sup>®</sup> - BROADWORKS SIP (RELEASE 11.1)	<b>ф</b> <sup>1</sup>		<b>e</b> <sup>1</sup>	<b>#</b> <sup>1</sup>
NORTEL NETWORKS - MCS 5100 & 5200	<b>.</b>	<b>•</b> <sup>1</sup>	<b>#</b> <sup>1</sup>	<b>#</b> <sup>1</sup>
SYLANTRO – SIP (VERSION 3.0.2)	<b>•</b> <sup>1</sup>	<b>#</b> <sup>1</sup>	<b>#</b> <sup>1</sup>	<b>#</b> <sup>1</sup>
ASTERISK	<b>₽</b> <sup>2</sup>	<b>•</b> <sup>2</sup>	<b>₽</b> <sup>2</sup>	<b>#</b> <sup>2</sup>

<sup>1</sup> Currently undergoing certification - Q2 2005

<sup>2</sup> Field tested

#### Protocols / Codecs

- » IETF SIP (RFC3261)
- » G.711 µ-law / A-law
- » G.729

#### Feature Highlights\*

- » Personal directory
- » Call forward
- » Call transfer
- » Call waiting
- » Caller and calling line information
- » Callers log
- » Conference
- » Redial list
- » Live dial pad or pre-dial support
- » Broadsoft's BroadWorks enhanced SIP supports Intercom, Shared Call Appearances, CommPilot Call Manager
- » Nortel's MCS SIP support Conferencing, Voicemail, and NAT Traversal support

#### Package Contents

- » 9112i IP Telephone
- » Desk Stand
- » AC wall adapter
- » Quick Installation Guide
- » Network Cable
- \* Feature availability dependent on IP telephony system



06/05

### For more information, contact your Aastra Telecom representative, or call +1 905 760-4200.

COPYRIGHT (C) 2005 AASTRA TELECOM. ALL RIGHTS RESERVED. INFORMATION IN THIS DOC-UMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. AASTRA TELECOM ASSUMES NO RESPON-SIBILITY FOR ANY ERRORS THAT MAY APPEAR IN THIS DOCUMENT. PRODUCT CAPABILITIES DESCRIBED IN THIS DOCUMENT PERTAIN SOLELY TO AASTRA TELECOM'S MARKETING ACTIV-ITIES IN THE U.S AND CANADA. AVAILABILITY IN OTHER MARKETS MAY VARY.